

MODEL	LT-168F
Engine Type	Air-Cooled; 4 Stroke OHV; Singlecylinder
Bore X Store	68 x 45(mm)
Displacement	163cc
Compression Ratio	8:5:1
Max. Power Output	5.5HP(4.1KW)
Rated Power Output	4.0HP(3.0KW)
Max. Torque	10.8N.m
Ignition System	Transistor Magneto
Starting System	Recoil Start
Engine Oil Capacity	0.6L
Fuel Capacity	3.6L
Min. Fuel Consumption	360g/kw/h
Net Weight (KG)	15

MODEL	LT-170F
Engine Type	Air-Cooled; 4 Stroke OHV; Singlecylinder
Bore X Store	70x54(mm)
Displacement	210cc
Compression Ratio	8:5:1
Max. Power Output	7.0HP(5.1KW)
Rated Power Output	6.0HP(4.4KW)
Max. Torque	14N.m
Ignition System	Transistor Magneto
Starting System	Recoil Start
Engine Oil Capacity	0.6L
Fuel Capacity	3.6L
Min. Fuel Consumption	360g/kw/h
Net Weight (KG)	16

MODEL	LT-188F
Engine Type	Air-Cooled; 4 Stroke OHV; Singlecylinder
Bore X Store	88 x 64(mm)
Displacement	389cc
Compression Ratio	8:0:1
Max. Power Output	13HP(9.6KW)
Rated Power Output	11.7HP(8.6KW)
Max. Torque	26.5N.m
Ignition System	Transistor Magneto
Starting System	Recoil Start
Engine Oil Capacity	1.1 L
Fuel Capacity	6.5 L
Min. Fuel Consumption	325g/kw/h
Net Weight (KG)	31

